

# INVERELL

ZERO CLEARANCE



Big, bold and striking, the Inverell adds great visual impact and plenty of heat for large, spacious areas.

- Efficiently heats areas up to 250m<sup>2</sup>
- Central Heating Appliance
- Zero Clearance as a standard
- For built-in cavity application only
- Flexible Ducting x 2 - The ducting is to be vented in the same room or an adjacent room



FINISH	VHT Black
FIREBOX	Steel
ESTIMATE PEAK OUTPUT	25kW
APPROX. HEAT AREA	250m <sup>2</sup>
EMISSIONS	N/A
EFFICIENCY	N/A
DIMENSIONS (WxDxH)	860 x 600 x 794mm
FASCIA DIMENSIONS (WxDxH)	814 x 6 x 692mm
LOG SIZE	560mm
WEIGHT	180kg
FLUE SPIGOT SIZE	6"/150mm

Minimum distance to heat sensitive materials (mm) and floor protector sizes as per standard AS/NZS 2918:2001

NOTE: INSULATED FLOOR PROTECTORS

For detailed design and specifications of insulated floor protector required please refer to the installation manual.

MODEL	TYPE	D	H	W	F	FH	FW	FF	HW*	HD*
I9000	INBUILT	600	794	860	248	692	814	352	1000	300

